DATA BULLETIN

Slip Lock®

Differential Additive

AMSOIL Slip Lock® Differential Additive (ADA) is formulated with advanced friction modifiers and is designed to eliminate gear-housing chatter in cars, trucks and SUVs equipped with clutch-type limited-slip differentials.



AMSOIL Slip Lock Differential Additive is formulated for use with both synthetic and petroleum gear lubricants and safely replaces manufacturer-recommended friction modifiers. Its convenient squeeze-tube packaging provides quick and easy application to the gear housing. One four-ounce tube of Slip Lock treats differential capacities of two to four quarts. It is not for use in automatic transmissions or other applications requiring automatic transmission fluid.

NOTE: AMSOIL synthetic gear lubes do not require this additive. However, not all differentials respond the same and the addition of AMSOIL Slip Lock will eliminate chatter in mechanically sound differentials.

Daryl Zebrasky

AMSOIL Regulatory Compliance

- **Contains** advanced friction modifiers
- **Helps** eliminate gear housing chatter
- **Recommended** for cars, trucks and SUVs



AMSOIL products and Dealership information are available from your local full-service AMSOIL Dealer.

AMSOIL INC., 925 Tower Ave., Superior, WI 54880 • 715-392-7101 • Printed in the USA.
© 2016, AMSOIL INC. All rights reserved. The AMSOIL logo is a registered trademark of AMSOIL INC.